

## NCE N-Channel Super Trench III Power MOSFET

### Description

The series of devices uses **Super Trench III** technology that is uniquely optimized to provide the most efficient high frequency switching performance. Both conduction and switching power losses are minimized due to an extremely low combination of  $R_{DS(ON)}$  and  $Q_g$ . This device is ideal for high-frequency switching and synchronous rectification.

### Application



- DC/DC Converter
- Ideal for high-frequency switching and synchronous rectification

### General Features

- $V_{DS} = 150V, I_D = 175A$   
 $R_{DS(ON)} = 3.6m\Omega$ , typical @  $V_{GS} = 10V$
- Excellent gate charge x  $R_{DS(on)}$  product(FOM)
- Very low on-resistance  $R_{DS(on)}$
- 175 °C operating temperature
- Pb-free lead plating

**100% UIS TESTED!**  
**100% ΔVds TESTED!**

### TO-263-2L



Schematic Diagram

### Package Marking and Ordering Information

| Device Marking | Device        | Device Package | Reel Size | Tape width | Quantity |
|----------------|---------------|----------------|-----------|------------|----------|
| NCEP048NH150D  | NCEP048NH150D | TO-263-2L      | -         | -          | -        |

### Absolute Maximum Ratings ( $T_c = 25^\circ C$ unless otherwise noted)

| Parameter   | Symbol             | Limit      | Unit          |
|---|--------------------|------------|---------------|
| Drain-Source Voltage                              | $V_{DS}$           | 150        | V             |
| Gate-Source Voltage                               | $V_{GS}$           | $\pm 20$   | V             |
| Drain Current-Continuous                          | $I_D$              | 175        | A             |
| Drain Current-Continuous( $T_c = 100^\circ C$ )   | $I_D(100^\circ C)$ | 122        | A             |
| Pulsed Drain Current                              | $I_{DM}$           | 700        | A             |
| Maximum Power Dissipation                         | $P_D$              | 323        | W             |
| Derating factor                                   |                    | 2.15       | W/ $^\circ C$ |
| Single pulse avalanche energy <sup>(Note 1)</sup> | $E_{AS}$           | 1536       | mJ            |
| Operating Junction and Storage Temperature Range  | $T_J, T_{STG}$     | -55 To 175 | $^\circ C$    |

### Thermal Characteristic

|                                      |                 |      |              |
|--------------------------------------|-----------------|------|--------------|
| Thermal Resistance, Junction-to-Case | $R_{\theta JC}$ | 0.46 | $^\circ C/W$ |
|--------------------------------------|-----------------|------|--------------|

## Electrical Characteristics (T<sub>c</sub>=25°C unless otherwise noted)


| Parameter                                 | Symbol              | Condition   | Min | Typ  | Max  | Unit |
|---|---------------------|---|-----|------|------|------|
| <b>Off Characteristics</b>                |                     |   |     |      |      |      |
| Drain-Source Breakdown Voltage            | BV <sub>DSS</sub>   | V <sub>GS</sub> =0V, I <sub>D</sub> =250μA  | 150 | -    | -    | V    |
| Zero Gate Voltage Drain Current           | I <sub>DSS</sub>    | V <sub>DS</sub> =150V, V <sub>GS</sub> =0V  | -   | -    | 1    | μA   |
| Gate-Body Leakage Current                 | I <sub>GSS</sub>    | V <sub>GS</sub> =±20V, V <sub>DS</sub> =0V  | -   | -    | ±100 | nA   |
| <b>On Characteristics</b>                 |                     |   |     |      |      |      |
| Gate Threshold Voltage                    | V <sub>GS(th)</sub> | V <sub>DS</sub> =V <sub>GS</sub> , I <sub>D</sub> =250μA                                | 2.5 | 3.5  | 4.5  | V    |
| Drain-Source On-State Resistance          | R <sub>DS(ON)</sub> | V <sub>GS</sub> =10V, I <sub>D</sub> =20A   | -   | 3.6  | 4.8  | mΩ   |
| Forward Transconductance                  | g <sub>FS</sub>     | V <sub>DS</sub> =10V, I <sub>D</sub> =40A   | -   | 75   | -    | S    |
| <b>Dynamic Characteristics</b>            |                     |   |     |      |      |      |
| Input Capacitance                         | C <sub>iss</sub>    | V <sub>DS</sub> =75V, V <sub>GS</sub> =0V,<br>F=1.0MHz                                  | -   | 7150 | -    | PF   |
| Output Capacitance                        | C <sub>oss</sub>    |   | -   | 2050 | -    | PF   |
| Reverse Transfer Capacitance              | C <sub>rss</sub>    |   | -   | 47   | -    | PF   |
| <b>Switching Characteristics</b> (Note 2) |                     |   |     |      |      |      |
| Turn-on Delay Time                        | t <sub>d(on)</sub>  | V <sub>DD</sub> =75V, I <sub>D</sub> =75A<br>V <sub>GS</sub> =10V, R <sub>G</sub> =4.7Ω | -   | 30   | -    | nS   |
| Turn-on Rise Time                         | t <sub>r</sub>      |   | -   | 40   | -    | nS   |
| Turn-Off Delay Time                       | t <sub>d(off)</sub> |   | -   | 70   | -    | nS   |
| Turn-Off Fall Time                        | t <sub>f</sub>      |   | -   | 15   | -    | nS   |
| Total Gate Charge                         | Q <sub>g</sub>      | V <sub>DS</sub> =75V, I <sub>D</sub> =20A,<br>V <sub>GS</sub> =10V                      | -   | 106  | -    | nC   |
| Gate-Source Charge                        | Q <sub>gs</sub>     |   | -   | 36   | -    | nC   |
| Gate-Drain Charge                         | Q <sub>gd</sub>     |   | -   | 27   | -    | nC   |
| <b>Drain-Source Diode Characteristics</b> |                     |   |     |      |      |      |
| Diode Forward Voltage                     | V <sub>SD</sub>     | V <sub>GS</sub> =0V, I <sub>F</sub> =I <sub>S</sub>                                     | -   | -    | 1.2  | V    |
| Diode Forward Current                     | I <sub>S</sub>      |   | -   | -    | 175  | A    |
| Reverse Recovery Time                     | t <sub>rr</sub>     | T <sub>J</sub> = 25°C, I <sub>F</sub> = 100A  | -   | 108  | -    | nS   |
| Reverse Recovery Charge                   | Q <sub>rr</sub>     | di/dt = 100A/μs   | -   | 270  | -    | nC   |

### Notes:


1. EAS condition : T<sub>j</sub>=25°C, V<sub>DD</sub>=50V, V<sub>G</sub>=10V, L=0.5mH, R<sub>G</sub>=25Ω
2. Guaranteed by design, not subject to production
3. These curves are based on the junction-to-case thermal impedance which is measured with the device mounted to a large heatsink, assuming a maximum junction temperature of T<sub>J(MAX)</sub>=175°C. The SOA curve provides a single pulse rating.

## Test Circuit


### 1) $E_{AS}$ test Circuit




### 2) Gate charge test Circuit




### 3) Switch Time Test Circuit




## Typical Electrical and Thermal Characteristics




**Figure 1 Output Characteristics**




**Figure 4  $R_{dson}$ -Junction Temperature**




**Figure 2 Transfer Characteristics**




**Figure 5 Gate Charge**




**Figure 3  $R_{dson}$ - Drain Current**




**Figure 6 Source- Drain Diode Forward**




**Figure 7 Capacitance vs Vds**




**Figure 10 Power De-rating**




**Figure 8 Safe Operation Area** (Note3)




**Figure 11 Current De-rating**



**Figure 9 V<sub>GS(th)</sub>-Junction Temperature**




**Figure 12 BV<sub>DSS</sub>-Junction Temperature**



**Figure 13 Normalized Maximum Transient Thermal Impedance**

## TO-263-2L Package Information



| SYMBOL | DIMENSIONS |       |       |
|--------|------------|-------|-------|
|        | MIN.       | NOM.  | MAX.  |
| A      | 4.24       | 4.44  | 4.64  |
| A1     | 0.00       | 0.10  | 0.15  |
| b      | 0.70       | 0.80  | 0.90  |
| b1     | 1.20       | 1.55  | 1.75  |
| b2     | 1.20       | 1.45  | 1.70  |
| c      | 0.40       | 0.50  | 0.60  |
| c2     | 1.15       | 1.27  | 1.40  |
| D      | 8.82       | 8.92  | 9.02  |
| D1     | 6.86       | 7.65  | —     |
| E      | 9.96       | 10.16 | 10.36 |
| E1     | 6.89       | 7.77  | 7.89  |
| e      | 2.54 BSC   |       |       |
| H      | 14.61      | 15.00 | 15.88 |
| L      | 1.78       | 2.32  | 2.79  |
| L1     | 1.36 REF.  |       |       |
| L2     | 1.50 REF.  |       |       |
| L3     | 0.25 BSC   |       |       |
| Q      | 2.30       | 2.48  | 2.70  |

## Attention:

- Any and all NCE power products described or contained herein do not have specifications that can handle applications that require extremely high levels of reliability, such as life-support systems, aircraft's control systems, or other applications whose failure can be reasonably expected to result in serious physical and/or material damage. Consult with your NCE power representative nearest you before using any NCE power products described or contained herein in such applications.
- NCE power assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all NCE power products described or contained herein.
- Specifications of any and all NCE power products described or contained herein stipulate the performance, characteristics, and functions of the described products in the independent state, and are not guarantees of the performance, characteristics, and functions of the described products as mounted in the customer's products or equipment. To verify symptoms and states that cannot be evaluated in an independent device, the customer should always evaluate and test devices mounted in the customer's products or equipment.
- NCE power CO.,LTD. strives to supply high-quality high-reliability products. However, any and all semiconductor products fail with some probability. It is possible that these probabilistic failures could give rise to accidents or events that could endanger human lives, that could give rise to smoke or fire, or that could cause damage to other property. When designing equipment, adopt safety measures so that these kinds of accidents or events cannot occur. Such measures include but are not limited to protective circuits and error prevention circuits for safe design, redundant design, and structural design.
- In the event that any or all NCE power products(including technical data, services) described or contained herein are controlled under any of applicable local export control laws and regulations, such products must not be exported without obtaining the export license from the authorities concerned in accordance with the above law.
- No part of this publication may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying and recording, or any information storage or retrieval system, or otherwise, without the prior written permission of NCE power CO.,LTD.
- Information (including circuit diagrams and circuit parameters) herein is for example only ; it is not guaranteed for volume production. NCE power believes information herein is accurate and reliable, but no guarantees are made or implied regarding its use or any infringements of intellectual property rights or other rights of third parties.
- Any and all information described or contained herein are subject to change without notice due to product/technology improvement, etc. When designing equipment, refer to the "Delivery Specification" for the NCE power product that you intend to use.
- This catalog provides information as of Aug.2023. Specifications and information herein are subject to change without notice.